

MODE

SPECIFICATION SHEET

Product Code CMA010

Description

10AX 1 Gang 1 Way Plate Switch





General Information	
Dimensions	86mm x 86mm x 9.5mm
Material composition	Rear Housing: Nylon
	Front Plate: Urea
	Terminals: Brass
	Earth Strap: Mild Steel
	Terminal Screws: Steel and Yellow Passivated
	Silver "on-lay" copper/brass contacts
Back Box Depth	16mm – 47mm
Cable Size	4 x 1.5mm ² or 2 x 2.5mm ²
Terminal Size	Live: 3.5mm
Load Rating	10AX (Suitable for Inductive loads)
Modular	Yes
Gang	1
1 Way	Yes
Intermediate	No
Warranty	20 Years Domestic

Standards	BS EN 60669

Additional Information	Ensure that the mains supply is isolated before commencing installation
	and refer to the circuit diagram supplied with the relevant product.
	Bare earth cables must always be covered with appropriate sleeving and
	wired to the earth terminal.
	All white moulded accessories are manufactured using Urea
	Formaldehyde, which has similar inherent properties to antimicrobial
	additives that inhibit the growth of infectious diseases. All products
	independently tested achieved a 99.9% kill rate across all four types of the
	strains of bacteria – MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.
	Interchangeable with switches in the Mini Grid system.

V1.0