



## **SPECIFICATION SHEET**

**Product Code** 

MD047\*#

Description

13A Fused Connection Unit Module







General Information	
Finishes Available	Replace * with: WH (White), BK (Black), PW (Polar White), and RD (Red)
'Ingot' Connection Unit with Black insert	Replace *# with: BKCH (Chrome), BKSC (Satin Chrome), BKBR (Brass),
	BKBN (Black Nickel), BKPN (Pearl Nickel), BKAB (Antique Brass), BKSB
	(Satin Brass), BKBS (Brushed Steel), and BKSS (Stainless Steel).
'Ingot' Connection with White Insert	Replace *# with: WHCH (Chrome), WHSC (Satin Chrome), WHBR (Brass),
	WHPN (Pearl Nickel), WHSB (Satin Brass), WHBS (Brushed Steel), and
	WHSS (Stainless Steel).
Dimensions	Module Width: 16mm, Rocker Height: 31.5mm
Terminal Size	Live: 3.5mm Diameter
Material composition	Rear Housing: Nylon
	Rocker: Urea or Urea + Stainless Steel Cover
	Terminals: Brass
	Terminal Screws: Steel and Yellow Passivated
	Silver "on-lay" copper/brass contacts.
Back Box Depth	25mm – 47mm
Cable Size	4 x 1.5mm <sup>2</sup> or 2 x 2.5mm <sup>2</sup> or 1 x 6mm <sup>2</sup>
Warranty	10 Years domestic

Standards	BS 1362
Additional Information	Ensure that the mains supply is isolated before commencing installation
	and refer to the circuit diagram supplied with the relevant product.
	These products are rated at 13A; therefore all terminals should not
	exceed the stated amperage.
	Bare earth cables must always be covered with green/yellow sleeving and
	wired to earth terminal.
	This range is not suitable for installation outdoors.

V1.0