



SPECIFICATION SHEET

Product Code PRW030 Description 13A 1 Gang Socket Outlet





| General Information | |
|----------------------|--|
| Dimensions | 86mm x 86mm x 11mm |
| Material composition | Rear Housing: Nylon |
| | Front Plate: Urea |
| | Terminals: Brass |
| | Earth Strap: Mild Steel |
| | Terminal Screws: Steel and Yellow Passivated |
| | Silver "on-lay" copper/brass contacts. |
| Back Box Depth | 25mm – 47mm |
| Cable Size | 4 x 2.5mm ² |
| Terminal Size | Live: 5mm |
| | Neutral: 5mm |
| | Earth: 5mm |
| Switched | No |
| Double Pole | No |
| Twin Earth | No |
| Clean Earth | No |
| Neon | No |
| Shutters | Yes |
| Warranty | 20 Years Domestic |

| Standards | BS 1363 |
|-----------|---------|
| | |

| Additional Information | Ensure that the mains supply is isolated before commencing installation |
|------------------------|--|
| | and refer to the circuit diagram supplied with the relevant product. |
| | Bare earth cables must always be covered with appropriate sleeving and |
| | wired to the earth terminal. |
| | All white moulded accessories are manufactured using Urea |
| | Formaldehyde, which has similar inherent properties to antimicrobial |
| | additives that inhibit the growth of infectious diseases. All products |
| | independently tested achieved a 99.9% kill rate across all four types of the |
| | strains of bacteria – MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae |

V1.0