



SPECIFICATION SHEET

Product Code

MD003*

Description

10AX 2 Way Keyswitch Module







General Information	
Finishes Available	Replace * with: WH (White), BK (Black), PW (Polar White), CH (Chrome), SC (Satin Chrome), BR (Brass), BN (Black Nickel), PN (Pearl Nickel), AB (Antique Brass), SB (Satin Brass), BS (Brushed Steel),
	and SS (Stainless Steel).
Dimensions	Module Width: 16mm, Rocker Height: 31.5mm
Terminal Size	Live 3.5mm Diameter
Material composition	Rear Housing: Nylon
	Rocker: Urea or Urea + Stainless Steel Cover
	Terminals: Brass
	Terminal Screws: Steel and Yellow Passivated
	Silver "on-lay" copper/brass contacts.
Back Box Depth	16mm – 47mm
Cable Size	4 x 1.5mm ² or 2 x 2.5mm ² or 1 x 6mm ²
Warranty	10 Years domestic

Standards	BS EN 60669
Additional Information	Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram supplied with the relevant product. These products are rated at 10A; therefore all terminals should not exceed the stated amperage. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. All white and anthracite grey moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases. All products independently tested achieved a 99.9% kill rate across all four types of the strains of bacteria – MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae
	Fileunioniae

V1.0