

Enclosed Changeover Switch

NLSWC1002E

- Under Load Operation
- Earth Terminal Included
- Captive + / - Terminal Screws
- Padlockable in the OFF Position (up to 3 Padlocks)
- IP65 / Lid Interlocked with Switch in Position 1 and 2
- Manufactured to IEC60947-3
- Multiple Knock-outs
- 2 Pole Switch Ratings at AC-22



⚠ Important Safety Notice

It is the responsibility of the person installing the electrical equipment to ensure that the installation meets the requirements of the IET wiring regulations and is therefore 'fit for purpose'. Factors such as correct selection of components, cable sizing, protective devices and Earth bonding are all critical and should be checked prior to full testing and power-up. Any other regulations applicable to the equipment being installed such as the Machinery Directive and current health and safety legislation must also be adhered to. Terminals, including factory fitted, should be checked periodically to ensure correct tightness.






DO NOT USE POWER TOOLS ON THESE PRODUCTS

Electrical Ratings (According to IEC60947-3)

AC Rated Thermal Current I_{th} (40°C)	100A
Rated Insulation Voltage U_i (V)	690
Rated Impulse Withstand Voltage U_{imp} (kV)	8

AC Rated Operational Current I_e (A)

Rated Voltage	Utilization Category	I_e
415 VAC	AC22A	100



Connection Capacity

Rigid Cable (Cu) (mm ²)	35/50
Flexible Cable (Cu) (mm ²)	16/35

14/10/2014