DESE Storage Heater



Technical Details

Controls	Digitally controlled, Electronic Thermostat accurate to (±0.2°C). Setpoint range (7-26°C) Timer mode: 7 Day Programmable User Timer
Controller UI	•Graphical display with white backlight •Capacitive buttons with audio feedback •User replaceable battery (Coin-Type)
Controller Functions	Open window detection Automatic Charge Control Bluetooth for software updates
Safety Features	Electronic overheat protection. Additional electromechanical overheat protection. LVD and EMC compliance.
Storage Core	High-density bonded magnetite energy cells
Colour/ Finish	White (RAL 9016) 'Traffic White' Grill RAL7035 anodised
Battery Backup	3.3V coin cell battery to backup real time clock. Battery life > 5 years.
Supply	1/N/PE 230-240V / 50Hz (Peak / Off Peak) Class II
IP Rating	IPX4
Approvals	CE & BEAB
Warranty	2 Years
Country of	United Kingdom
Manufacturer	Denmans

Output										
Model No.	Input Rating +5%/ -10%	Output Rating	Maximum Storage Capacity (Wh)							
DESE050	1020W	500W	7140							
DESE070	1560W	700W	10920							
DESE100	2220W	1000W	15540							
DESE125	2760W	1250W	19320							
DESE150	3300W	1500W	23100							



Product Description

An advanced electric storage heater with a clean look and reliable performance. DESE storage heaters provide an upgraded and compliant replacement for older storage heaters.

Key Features

- Complies with Lot 20 of ERP Directive
- Programmable room temperatures with seven-day timer
- Efficient heating system with low running costs delivered by maximising the use of off-peak tariffs
- Dynamically stores the right amount of energy to heat a room
- Controllable electronic heat output to match user lifestyle
- Fan assisted to quickly, quietly and more effectively distribute heat
- Supplied with 40mm feet for weight distribution when secured to wall.
 Two feet positions available.
- · Slimline design that covers traditional storage heater fixing marks

Requires Energy Cell Packs to function Item: 047243 (included with purchase)

Dimensions SHELF W ISOmm (min) A B A B A Feet Position 1 shown

	Y											
Model/Item No. EAN-Code 5011139+Item No.)	080592	DESE050	080608	DESE070	081223	DESE100	080615	DESE125	081070	DESE150		
Feet Position 1 'A/B'	167/124		167/185		167/246		160/314		160/375			
Feet Position 2 'A/B'	93/198		93/259		93/320		100/374		100/435			
Output (kW)	0.50		0.70		1.00		1.25		1.50			
Height (mm)	749		749		749		749		749			
Width 'W' (mm)	581		703		825		947		1069			
Depth (mm)	182		18	182		182		182		182		
Weight (KG)	63		8	5	107		133		155			
Energy Cell Packs Required	4		(3	8		10		12			
Packaging Details												
Height (mm) 838		38	838		838		838		838			
Width (mm)	703		825		947		1069		1191			
Depth (mm)	245		245		245		245		245			
Packed Weight (KG) 23		3	26		28		34		36			
Ti	5		5		5		4		4			
Hi	2		2		2		2		2			
Pallet Quantity (2.4m high)		0	10		10		8		8			