


# Product datasheet

Specifications



## Terminal block - 125 A - 10 holes

Local distributor code: 1516360 14977

### Main

Range	Prisma
Product or component type	Terminal block

### Complementary

[In] rated current	125 A
[Ui] rated insulation voltage	500 V
Number of terminal blocks	1 (screw) with 10 outgoers
Distribution block outgoers	4 x 16 mm² 1 x 35 mm² 5 x 10 mm²
Range compatibility	Prisma G Opale Pragma

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	50.0 g
Package 1 Height	2 cm
Package 1 width	3 cm
Package 1 Length	12 cm
Unit Type of Package 2	S04
Number of Units in Package 2	250
Package 2 Weight	15.766 kg
Package 2 Height	30 cm
Package 2 width	40 cm
Package 2 Length	60 cm
Unit Type of Package 3	BB1
Number of Units in Package 3	5
Package 3 Weight	300.0 g
Package 3 Height	5.5 cm

Package 3 width	11 cm
Package 3 Length	14.5 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------