


# Product datasheet

Specifications



## TAP OFF UNIT 160A FUSE BS88

Local distributor code: 2222420 KSB160SG4

### Main

Range of product	Canalis
Range compatibility	KT busbar trunking KS busbar trunking
Product or component type	Tap-off unit
Busbar trunking compatibility	Canalis KS busbar trunking plug-in Canalis KT busbar trunking with KS type plug-in
[Ie] rated operational current	160 A at 35 °C
Protection type	fuse isolator: BS88 fuse, size B1 conforming to BS fuse isolator: BS88 fuse, size B2 conforming to BS
Provided equipment	fuse to be ordered separately
Mounting mode	Plug-in with fixed polarity
Tap-off unit polarity	3L+N+PE
Colour	White (RAL 9001)

### Complementary

Device application	Medium power distribution
[Ue] rated operational voltage	230...690 V depending on protective device
[Uiimp] rated impulse withstand voltage	6.8 kV
[Ui] rated insulation voltage	690 V depending on protective device
Network frequency	50/60 Hz
Electrical connection	Copper cable lug - ISO25 50 mm <sup>2</sup> flexible Copper cable lug - ISO25 50 mm <sup>2</sup> rigid
Door/Cover opening side	Right
Tap-off unit disconnection mode	By opening the door
Standards	IEC 61439-1 IEC 61439-6
Body material	Metal
Width	482 mm
Depth	207 mm
Depth (door open)	577.5 mm
Height	332 mm

Net weight	11 kg
------------	-------

## Environment

Earthing system	TT TN-S IT
IP degree of protection	IP55 conforming to IEC 60529
IK degree of protection	IK08 conforming to IEC 62262

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	9.858 kg
Package 1 Height	29.5 cm
Package 1 width	33.5 cm
Package 1 Length	50.5 cm
Unit Type of Package 2	P12
Number of Units in Package 2	8
Package 2 Weight	97.0 kg
Package 2 Height	71 cm
Package 2 width	80 cm
Package 2 Length	120 cm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

## Contractual warranty

Warranty	18 months
----------	-----------