

Product datasheet

Specifications



Thorsman - TP 2B - wall plug - without screw - set of 100

Local distributor code: 2227331 1005008

Main

Range of product	Thorsman
Product or component type	Wall plug
Device short name	TP
Provided equipment	Without screw
Device application	Lightweight installation
Drilling diameter	8 mm concrete 8 mm brick 7 mm ALC concrete
Minimum drilling depth	45 mm
Screw diameter	5...6 mm
Material	PEHD (polyethylene high density)

Complementary

Practical load capacity	Shear: 1.2 kN for concrete C25 4.5) Pull-out load: 0.8 kN for concrete C25 6) Shear: 0.7 kN for solid brick 4.5) Pull-out load: 0.4 kN for solid brick 6) Shear: 0.25 kN for low density concrete 500 and expanded clay 4.5) Pull-out load: 0.1 kN for low density concrete 500 and expanded clay 6)
Practical load capacity	Shear: 120 kg for concrete C25 4.5) Pull-out load: 80 kg for concrete C25 6) Shear: 70 kg for solid brick 4.5) Pull-out load: 40 kg for solid brick 6) Shear: 25 kg for low density concrete 500 and expanded clay 4.5) Pull-out load: 10 kg for low density concrete 500 and expanded clay 6)
Colour tint	Brown
Ambient air temperature for operation	-50...80 °C
Diameter	8 mm
Length	40 mm

Environment

Quantity per set	Set of 100
Sale per indivisible quantity	10
Net weight	0.00138 kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	1.6 g
Package 1 Height	1 cm
Package 1 width	1 cm
Package 1 Length	4 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	100
Package 2 Weight	166.0 g
Package 2 Height	4.6 cm
Package 2 width	6 cm
Package 2 Length	21.8 cm
Unit Type of Package 3	BB2
Number of Units in Package 3	1000
Package 3 Weight	1.614 kg
Package 3 Height	12.5 cm
Package 3 width	21.5 cm
Package 3 Length	22 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------