

Product datasheet

Specifications



FEED UNIT 40A LEFT MOUNTING

Local distributor code: 21470091 KBA40ABG4W



Main

Range of product	Canalis
Product or component type	Feed unit
BAR MATERIAL	Aluminium
Product compatibility	KBA
[Ie] rated operational current	25 A 40 A
Mounting location	Left
Colour	White (RAL 9003)

Complementary

Protection type	Without protection
[Ue] rated operational voltage	230...400 V
Connections - terminals	Terminal block - Pg 21 - screw clamp connector for 10 mm²
Control type	Without
Number of circuits	1
Provided equipment	End cover
Mounting mode	By screws
Mounting support	Busbar
Standards	IEC 60439-2 IEC 61439-6
Width	300 mm
Depth	75.5 mm
Height	78.5 mm
Net weight	400 g

Environment

IP degree of protection	IP55 conforming to IEC 60529
-------------------------	------------------------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Package 1 Weight	450.0 g
Package 1 Height	7.5 cm
Package 1 width	7.5 cm
Package 1 Length	37 cm
Unit Type of Package 2	P06
Number of Units in Package 2	120
Package 2 Weight	63.0 kg
Package 2 Height	75 cm
Package 2 width	60 cm
Package 2 Length	80 cm
Unit Type of Package 3	S03
Number of Units in Package 3	15
Package 3 Weight	7.0 kg
Package 3 Height	30 cm
Package 3 width	30 cm
Package 3 Length	40 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free product

Contractual warranty

Warranty	18 months
----------	-----------

