

# Product datasheet

Specifications



## END FEED UNIT 63 A

Local distributor code: 2224619 KNA63AB4



### Main

Range of product	Canalis
Product name	KN
Product or component type	Feed unit
BAR MATERIAL	Plastic
Product compatibility	KN
[Ie] rated operational current	40 A 63 A
Mounting location	Left Right
Colour	White (RAL 9001)

### Complementary

Protection type	Without protection
[Ue] rated operational voltage	230...500 V
Connections - terminals	Terminal block for 16 mm <sup>2</sup> flexible Terminal block for 25 mm <sup>2</sup> rigid
Control type	Without
Number of circuits	1
Provided equipment	End cover
Mounting mode	By clips
Mounting support	Busbar
Standards	IEC 61439-6 IEC 60439-2
Width	265 mm
Depth	71 mm
Height	92 mm
Net weight	580 g

### Environment

IP degree of protection	IP55 conforming to IEC 60529
IK degree of protection	IK08 conforming to IEC 62262

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	651.0 g
Package 1 Height	8 cm
Package 1 width	11 cm
Package 1 Length	29.9 cm
Unit Type of Package 2	P06
Number of Units in Package 2	36
Package 2 Weight	29.818 kg
Package 2 Height	37.4 cm
Package 2 width	60 cm
Package 2 Length	80 cm
Package 3 Height	53 cm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free product

## Contractual warranty

Warranty	18 months
----------	-----------