

# Product datasheet

Specifications



## Spacial SF enclosure with mounting plate - assembled - 1800x1000x400 mm

Local distributor code: 22145846 NSYSF1810402DP

### Main

|                           |  |
|---------------------------|--|
| Range                     | Spacial  |
| Extended range            | Spacial SF   |
| Application               | Multi-purpose  |
| Product or component type | Suitable enclosure   |
| Enclosure nominal height  | 1800 mm  |
| Enclosure nominal width   | 1000 mm  |
| Enclosure nominal depth   | 400 mm   |
| Enclosure mounting        | Floor-standing   |
| Device composition        | 2 sliding rails<br>4 mounting plate bracket<br>1 structure<br>1 rear panel<br>1 roof<br>1 mounting plate<br>2 door<br>1 locking system with handle<br>1 blocking system: left door |

### Complementary

|                             |   |
|-----------------------------|---|
| Structure type              | Panels and doors built into the structure<br>Vertical uprights joined with top and bottom frames<br>Formed from a single section<br>Perforated structure with a pitch of 25 mm  |
| Door type                   | Plain front   |
| Number of doors             | Front face: 2 door(s)   |
| Door opening side           | Left (120 °)<br>Right (120 °)   |
| Lock type                   | 4 points lock, handle with 5 mm double bar insert front right door  |
| Mounting plate description  | Plain   |
| Type of gland plate         | Without gland plate   |
| Accessibility for operation | Sides of enclosure<br>Rear<br>Front   |
| Removable parts             | Door by screws hinge<br>Mounting plate by screws mounting plate bracket<br>Rear panel by screws<br>Roof by screws<br>Mounting plate bracket by screws<br>Sliding rail by screws |
| Material                    | Frame: galvanised steel   |

Uprights: galvanised steel  
Door: sheet steel  
Panels: sheet steel  
Hinge: zamak  
Handle: polyamide 6 with 30 % fibre glass

|                |  |
|----------------|--|
| Surface finish | Epoxy-polyester powder                                 |
| Colour         | Enclosure: grey (RAL 7035)<br>Handle: black (RAL 9005) |
| Net weight     | 147.462 kg   |

## Environment

|                           |                              |
|---------------------------|------------------------------|
| Standards                 | IEC 62208                    |
| NEMA degree of protection | NEMA 3R/12                   |
| IP degree of protection   | IP55 conforming to IEC 60529 |
| IK degree of protection   | IK10 conforming to IEC 62262 |

## Packing Units

|                              |          |
|------------------------------|----------|
| Unit Type of Package 1       | PCE      |
| Number of Units in Package 1 | 1        |
| Package 1 Weight             | 147.0 kg |
| Package 1 Height             | 194 cm   |
| Package 1 width              | 104 cm   |
| Package 1 Length             | 50 cm    |

## Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product   |
| REACH Regulation           | <a href="#">REACH Declaration</a>   |
| REACH free of SVHC         | Yes   |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope)<br><a href="#">EU RoHS Declaration</a>                     |
| Mercury free               | Yes   |
| RoHS exemption information | <a href="#">Yes</a>   |
| China RoHS Regulation      | <a href="#">China RoHS declaration</a><br>Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>   |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|