



TAPOFF UNIT 32 A WITH ISOLATOR FOR BS FUSES

Local distributor code: 2224583 KNB32SG4

Main

Range of product	Canalis
Range compatibility	KN busbar trunking
Product or component type	Tap-off unit
Busbar trunking compatibility	Canalis KN busbar trunkingplug-in
[le] rated operational current	32 A at 35 °C
Protection type	fuse isolator: BS88 fuse, size A1 conforming to BS
Provided equipment	fuse to be ordered separately
Mounting mode	Plug-in with fixed polarity
Tap-off unit polarity	3L+N+PE 3L+PE
Colour	White (RAL 9001)

Complementary

Low power distribution
230500 V depending on protective device
4.6 kV
500 V depending on protective device
50/60 Hz
Cable clamp terminal - ISO50 10 mm² flexible Cable clamp terminal - ISO50 10 mm² rigid
Right
By opening the door
IEC 61439-1 IEC 61439-6
344 mm
101 mm
432.5 mm
165 mm
1.5 kg

Environment

IP degree of protection	IP55 conforming to IEC 60529
IK degree of protection	IK08 conforming to IEC 62262

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	1.55 kg
Package 1 Height	13.7 cm
Package 1 width	16.6 cm
Package 1 Length	34.6 cm
Unit Type of Package 2	P12
Number of Units in Package 2	52
Package 2 Weight	99.0 kg
Package 2 Height	80 cm
Package 2 width	80 cm
Package 2 Length	120 cm

Offer Sustainability

Green Premium product
REACh Declaration
Yes
Compliant EU RoHS Declaration
Yes
Yes
Yes
China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Product Environmental Profile
The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------