


Product datasheet

Specifications



Terminal block - 125 A - 6 holes

Local distributor code: 1516357 14976



Main

Range	Prisma
Product or component type	Terminal block

Complementary

[In] rated current	125 A
[Ui] rated insulation voltage	500 V
Number of terminal blocks	1 (screw) with 6 outgoing
Distribution block outgoing	1 x 35 mm ² 2 x 16 mm ² 3 x 10 mm ²
Range compatibility	Prisma G Opale Pragma

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	35.0 g
Package 1 Height	2 cm
Package 1 width	3 cm
Package 1 Length	7 cm
Unit Type of Package 2	S04
Number of Units in Package 2	250
Package 2 Weight	9.716 kg
Package 2 Height	30 cm
Package 2 width	40 cm
Package 2 Length	60 cm
Unit Type of Package 3	BB1
Number of Units in Package 3	5
Package 3 Weight	179.0 g
Package 3 Height	2.5 cm

Package 3 width	12 cm
Package 3 Length	16 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------