

END FEED BOX 100 A



Local distributor code: 2221832 KSA100AB4

Main

Range of product	Canalis
Product name	KS
Product or component type	Feed unit
BAR MATERIAL	Aluminium
Product compatibility	KS
[le] rated operational current	100 A
Mounting location	Right Left
Colour	White (RAL 9001)

Complementary

•	
Protection type	Without protection
[Ue] rated operational voltage	230690 V
Connections - terminals	Terminal block for 16 mm² flexible Terminal block for 16 mm² rigid
Control type	Without
Number of circuits	1
Provided equipment	End cover
Mounting mode	By screws
Mounting support	Busbar
Standards	IEC 60439-2 IEC 61439-6
Width	390 mm
Depth	112 mm
Height	212 mm
Body material	Plastic
Net weight	1.85 kg

Environment

IP degree of protection	IP55 conforming to IEC 60529
IK degree of protection	IK08 conforming to IEC 62262

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	2.006 kg
Package 1 Height	12.5 cm
Package 1 width	22 cm
Package 1 Length	39 cm
Unit Type of Package 2	PAL
Number of Units in Package 2	30
Package 2 Weight	66.565 kg
Package 2 Height	40 cm
Package 2 width	60 cm
Package 2 Length	89.5 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free product

Contractual warranty

Warranty	18 months
<u> </u>	

Product datasheet

KSA100AB4

Dimensions Drawings

Dimensions

