

Product datasheet

Specifications



Acti 9 - MIN - electromechanical timer - adjustable from 1 to 7 minutes

Local distributor code: 1506493 15363

Main

Range of product	Acti 9
Product name	Acti 9 MIN
Device short name	MIN
Product or component type	Electromechanical timer
Colour tint	White (RAL 9003)

Complementary

Device application	Building
Load type	Parallel-corrected fluorescent tube 14 x 40 W 4.7 µF Parallel-corrected fluorescent tube 10 x 58 W 7 µF Parallel-corrected fluorescent tube 3.0 x 100 W 18 µF 230 V AC halogen lamp 2300 W 230 V AC incandescent lamp 2300 W Fluocompact lamp 2300 VA Compact fluorescent lamp 21 x 7 W Compact fluorescent lamp 13 x 11 W Compact fluorescent lamp 10 x 15 W Compact fluorescent lamp 7 x 20 W LED lamp < 2 W 30 W LED lamp > 2 W 300 W
Power consumption in VA	1 VA
Maximum switching current	16 A - 230 V AC pf = 1
[Ue] rated operational voltage	230 V AC at 50 Hz
Time delay	Adjustable from 1 to 7 minutes
Mounting support	DIN rail
9 mm pitches	2
Connections - terminals	Screw terminals - <= 6 mm²
Width	18 mm
Height	83 mm
Depth	68 mm
Net weight	84 g

Environment

Ambient air temperature for operation	-10...50 °C
IP degree of protection	IP20 B

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	85.0 g
Package 1 Height	2 cm
Package 1 width	7 cm
Package 1 Length	9.5 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	895.0 g
Package 2 Height	7.5 cm
Package 2 width	10.5 cm
Package 2 Length	22 cm
Unit Type of Package 3	S03
Number of Units in Package 3	110
Package 3 Weight	10.781 kg
Package 3 Height	30 cm
Package 3 width	30 cm
Package 3 Length	40 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Contractual warranty

Warranty	18 months
----------	-----------