

Product datasheet

Specifications



FA/LA MOLDED CASE CIRCUIT BREAKER, 415/240V, 400A, 3P

Local distributor code: 2026655 SLA3400

Main

Product or component type	Circuit breaker
Trip Unit Technology	Thermal-magnetic

Complementary

[In] rated current	400 A
Number of Poles	3P
Breaking capacity code	A
Mounting Mode	I-Line
Magnetic Hold Current	2000 A
Magnetic Tripping Current	4000 A
Electrical connection	Lugs load I-Line connection line
Terminal identifier	AL400LA
Tightening torque	13 N.m for 42...304 mm² (AWG 1...600 kcmil) 13 N.m for 42...127 mm² (AWG 1...250 kcmil)
Height	320.04 mm
Width	317.50 mm
Depth	505.46 mm

Environment

Certifications	IEC CE
----------------	-----------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	8.25 kg
Package 1 Height	22.86 cm
Package 1 width	29.464 cm
Package 1 Length	44.45 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
PVC free	Yes
Halogen content performance	Halogen free plastic parts product

Contractual warranty

Warranty	18 months
----------	-----------