

Product datasheet

Specifications



CONNECTOR 32A 5 MODULES

Local distributor code: 2222352 KSB32CM55

Main

| | |
|--------------------------------|--|
| Range of product | Canalis |
| Range compatibility | KS busbar trunking |
| Product or component type | Tap-off unit |
| Busbar trunking compatibility | Canalis KS busbar trunkingplug-in |
| [Ie] rated operational current | 32 A |
| Protection type | Circuit breaker: miniature circuit breaker (MCB) |
| Mounting mode | Plug-in with fixed polarity |
| Tap-off unit polarity | 3L+N+PE |
| Colour | White (RAL 9001) |

Complementary

| | |
|--|--|
| Device application | Medium power distribution |
| Provided equipment | circuit-breaker to be ordered separately blanking plate |
| [Ue] rated operational voltage | 230...690 V depending on protective device |
| [Uimp] rated impulse withstand voltage | 6.8 kV |
| [Ui] rated insulation voltage | 400 V depending on protective device 500 V depending on protective device 690 V depending on protective device |
| Network frequency | 50/60 Hz |
| Electrical connection | Pre-wired terminal block - ISO32 6 mm² flexible Pre-wired terminal block - ISO32 10 mm² rigid |
| Door/Cover opening side | Front |
| Tap-off unit disconnection mode | By drawing out |
| Standards | IEC 61439-6 IEC 61439-1 |
| Body material | Plastic |
| 18 mm pitches | 5 |
| Width | 135 mm |
| Depth | 108 mm |
| Height | 175 mm |

| | |
|------------|--------|
| Net weight | 0.6 kg |
|------------|--------|

Environment

| | |
|-------------------------|------------------------------|
| Earthing system | TT TN-S IT |
| IP degree of protection | IP55 conforming to IEC 60529 |
| IK degree of protection | IK08 conforming to IEC 62262 |

Packing Units

| | |
|------------------------------|----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 725.0 g |
| Package 1 Height | 16.5 cm |
| Package 1 width | 15.5 cm |
| Package 1 Length | 18.5 cm |
| Unit Type of Package 2 | P12 |
| Number of Units in Package 2 | 119 |
| Package 2 Weight | 103.0 kg |
| Package 2 Height | 80 cm |
| Package 2 width | 80 cm |
| Package 2 Length | 120 cm |

Offer Sustainability

| | |
|-----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope) |
| Environmental Disclosure | Product Environmental Profile |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Halogen content performance | Halogen free plastic parts product |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|