



TeSys GV2 & GV3 - auxiliary contact - 1 NO/NC

Local distributor code: 381798219

TeSys TeSys Deca
GVAE
Auxiliary contact block
GV2L GV2P GV2RT GV3P GV3L GV2LE GV2ME
Front side
1 NO/NC
Set of 10

Complementary	
[Ui] rated insulation voltage	300 V conforming to UL 508 300 V conforming to CSA C22.2 No 14 250 V conforming to IEC 60947-1
[Ue] rated operational voltage	24240 V AC 2460 V DC
[Ith] conventional free air thermal current	2.5 A
Protection type	GG fuse 10 A GB2CB06 circuit breaker 10 A
Mechanical durability	100000 cycles
Minimum switching current	5 mA
Minimum switching voltage	17 V
Rated operational power in VA	120 VA at 110120 V AC-15 - electrical durability: 100000 cycles 120 VA at 230240 V AC-15 - electrical durability: 100000 cycles 48 VA at 24 V AC-15 - electrical durability: 100000 cycles 60 VA at 48 V AC-15 - electrical durability: 100000 cycles
Rated operational power in W	15 W at 48 V DC-13 - electrical durability: 100000 cycles 24 W at 24 V DC-13 - electrical durability: 100000 cycles 9 W at 60 V DC-13 - electrical durability: 100000 cycles
Tightening torque	1.4 N.m - on screw clamp terminals
Height	11 mm
Width	45 mm

Depth	29 mm
Net weight	0.02 kg
Environment	Named and another
Environmental characteristic	Normal environment
Product certifications	UKCA
Packing Units	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	13.0 g
Package 1 Height	1.1 cm
Package 1 width	6 cm
Package 1 Length	8 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	140.0 g
Package 2 Weight	2 cm
Package 2 width	16 cm
Package 2 Length	17 cm
Unit Type of Package 3	S02
	220
Number of Units in Package 3	
Package 3 Weight	3.385 kg
Package 3 Height	15 cm
Package 3 width	30 cm
Package 3 Length	40 cm
Offer Sustainability	
Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant
	EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Contractual warranty	
Warranty	18 months
