

# Product datasheet

Specifications



remote control source changeover,  
Transferpack, ACP plate and UA  
controller, 220 VAC to 240 VAC  
50/60 Hz

Local distributor code: 382193525 29472

## Main

|                                    |                                                                                                                             |
|------------------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| Range of product                   | NSX100...250<br>Compact NS100...630<br>MasterPact NW<br>MasterPact NT<br>NSX400...630<br>Compact NS630b...1600              |
| Product or component type          | Interface and control unit                                                                                                  |
| Accessory / separate part category | Interlocking accessory                                                                                                      |
| Range compatibility                | ComPact NS circuit breaker<br>ComPact NSX circuit breaker<br>MasterPact NT circuit breaker<br>MasterPact NW circuit breaker |
| Device short name                  | ACP + UA                                                                                                                    |
| [Us] rated supply voltage          | 220...240 V AC at 50/60 Hz                                                                                                  |

## Complementary

|                                             |                                                                                                                                                                                                                                                                                                                                                                               |
|---------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Operating mode                              | Automatic operation<br>Forced operation on normal source<br>Stop (both normal and replacement source off)<br>Forced operation on replacement source                                                                                                                                                                                                                           |
| Interlocked device                          | MasterPact NT<br>NSX400...630<br>MasterPact NW<br>NSX100...250<br>Compact NS100...630<br>Compact NS630b...1600                                                                                                                                                                                                                                                                |
| Selection modes                             | Circuit breaker on R<br>Circuit breaker on N                                                                                                                                                                                                                                                                                                                                  |
| Test function                               | By pressing the test button on the front of the controller                                                                                                                                                                                                                                                                                                                    |
| Complementary function                      | Voluntary transfer to replacement source (e.g. energy management commands)<br>Forced normal source if replacement source not operational during peak-tariff<br>Selection of type of normal source (single-phase or three-phase)<br>Setting of maximum startup time for the replacement source<br>Additional contact: transfer to replacement source only if contact is closed |
| Local signalling                            | On<br>Off<br>Fault trip                                                                                                                                                                                                                                                                                                                                                       |
| Input type                                  | Contacts customer voluntary order to transfer to source R                                                                                                                                                                                                                                                                                                                     |
| Output type                                 | Contacts customer: indication of operation in automatic or stop mode                                                                                                                                                                                                                                                                                                          |
| [Ith] conventional free air thermal current | 8 A                                                                                                                                                                                                                                                                                                                                                                           |
| [Ie] rated operational current              | AC-12: 4 A AC 440 V<br>AC-12: 5 A AC 380/415 V                                                                                                                                                                                                                                                                                                                                |

|                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|-----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                       | AC-12: 8 A AC 110 V<br>AC-12: 8 A AC 220/240 V<br>AC-12: 8 A AC 24 V<br>AC-12: 8 A AC 48 V<br>AC-13: 6 A AC 110 V<br>AC-13: 6 A AC 220/240 V<br>AC-13: 7 A AC 24 V<br>AC-13: 7 A AC 48 V<br>AC-14: 4 A AC 110 V<br>AC-14: 4 A AC 220/240 V<br>AC-14: 5 A AC 24 V<br>AC-14: 5 A AC 48 V<br>AC-15: 3 A AC 220/240 V<br>AC-15: 4 A AC 110 V<br>AC-15: 5 A AC 24 V<br>AC-15: 5 A AC 48 V<br>DC-12: 0.4 A DC 250 V<br>DC-12: 0.6 A DC 110 V<br>DC-12: 2 A DC 48 V<br>DC-12: 8 A DC 24 V<br>DC-13: 2 A 24 V |
| Product compatibility | Compact NS630b...1600<br>Compact NSX100...250<br>Compact NSX400...630                                                                                                                                                                                                                                                                                                                                                                                                                                 |

## Environment

|                         |                                                                                                                    |
|-------------------------|--------------------------------------------------------------------------------------------------------------------|
| Standards               | IEC 947-5-1                                                                                                        |
| IP degree of protection | IP20 connectors: conforming to EN 60529<br>IP40 front: conforming to EN 60529<br>IP30 side: conforming to EN 60529 |
| IK degree of protection | Front: IK07 conforming to EN 50102                                                                                 |

## Packing Units

|                              |          |
|------------------------------|----------|
| Unit Type of Package 1       | PCE      |
| Number of Units in Package 1 | 1        |
| Package 1 Weight             | 4.019 kg |
| Package 1 Height             | 12.7 cm  |
| Package 1 width              | 16 cm    |
| Package 1 Length             | 27.5 cm  |

## Offer Sustainability

|                            |                                                                                                                       |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                                                 |
| REACH Regulation           | <a href="#">REACH Declaration</a>                                                                                     |
| EU RoHS Directive          | Compliant<br><a href="#">EU RoHS Declaration</a>                                                                      |
| Mercury free               | Yes                                                                                                                   |
| RoHS exemption information | <a href="#">Yes</a>                                                                                                   |
| China RoHS Regulation      | <a href="#">China RoHS declaration</a><br>Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>                                                                         |
| Circularity Profile        | <a href="#">End of Life Information</a>                                                                               |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|