

Product datasheet

Specifications



Ultimate Slimline - unswitched fused connection - neon - white

Local distributor code: 382625938 GU5001

Main

Range	Ultimate
Device application	Protection
Aesthetic name	Slimline
Product or component type	Unswitched fused connection
Switch function	-
Colour tint	White

Complementary

Pilot light	Red neon indicator
Number of gangs	1 gang
Material	Urea (carbamide)
Mounting support	Wall mounted
Fixing mode	By screws
Rated current	13 A at 230 V AC
Connections - terminals	Screw terminals
Quantity per set	Set of 10
Height	86 mm
Width	86 mm
Depth	23 mm
Fuse type	Blade type

Environment

IP degree of protection	IP20
Standards	BS 1363

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	100.9 g
Package 1 Height	2.3 cm

Package 1 width	8.6 cm
Package 1 Length	8.6 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	1.087 kg
Package 2 Height	9.6 cm
Package 2 width	18.4 cm
Package 2 Length	13.1 cm
Unit Type of Package 3	CAR
Number of Units in Package 3	200
Package 3 Weight	22.4 kg
Package 3 Height	28.3 cm
Package 3 width	39.2 cm
Package 3 Length	50 cm

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration

Contractual warranty

Warranty	18 months
----------	-----------