

Product datasheet

Specifications



Ultimate Flat plate - switched socket - 1 gang - stainless steel

Local distributor code: 382626539 GU3210WSS

Main

Range	Ultimate
Device application	Power supply
Aesthetic name	Flat plate
Product or component type	Switched socket
Rated current	13 A at 230 V AC 50 Hz
Fixing mode	By screws M3.5 x 30 mm
Colour tint	Stainless steel

Complementary

Device presentation	Complete product
Outlet poles configuration	1P
Outlet standard description	3 pins
Outlet standard	British
Actuator	Rocker
Number of gangs	1 gang
Earth circuit	Standard earth
Pilot light	Without neon indicator
Device mounting	Wall mounted
Connections - terminals	Screw terminal
Material	Stainless steel
Quantity per set	Set of 1
Height	88 mm
Width	88 mm
Depth	30 mm
Socket number	1
Mounting mode	Horizontal

Environment

IP degree of protection	IP20
-------------------------	------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	166.5 g
Package 1 Height	4 cm
Package 1 width	9.5 cm
Package 1 Length	9.6 cm
Unit Type of Package 2	CAR
Number of Units in Package 2	100
Package 2 Weight	17.342 kg
Package 2 Height	21.5 cm
Package 2 width	42.5 cm
Package 2 Length	50 cm
Unit Type of Package 3	PAM
Number of Units in Package 3	1600
Package 3 Weight	297.481 kg
Package 3 Height	102.5 cm
Package 3 width	100 cm
Package 3 Length	120 cm

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration

Contractual warranty

Warranty	18 months
-----------------	-----------