


# Product datasheet

Specifications



vertical rear connections, 630 A to 1600 A, fixed circuit breaker, top mounting, 4 poles

Local distributor code: 383450092 33614

## Main

|                                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
|------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product or component type          | Rear connection                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Accessory / separate part category | Connection accessory                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Range compatibility                | ComPact NS630b...1600 circuit breaker<br>ComPact NS630b...1600 switch disconnecter<br>MasterPact NT circuit breaker<br>MasterPact NT switch disconnecter                                                                                                                                                                                                                                                                                                    |
| Poles description                  | 4P                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| [In] rated current                 | 630 A H1 fixed<br>630 A H2 fixed<br>630 A H3 fixed<br>630 A L1 fixed<br>630 A HA fixed<br>800 A H1 fixed<br>800 A H2 fixed<br>800 A H3 fixed<br>800 A L1 fixed<br>800 A HA fixed<br>1000 A H1 fixed<br>1000 A H2 fixed<br>1000 A H3 fixed<br>1000 A L1 fixed<br>1000 A HA fixed<br>1250 A H1 fixed<br>1250 A H2 fixed<br>1250 A H3 fixed<br>1250 A HA fixed<br>1600 A H1 fixed<br>1600 A H2 fixed<br>1600 A H3 fixed<br>1600 A HA fixed<br>1600 A H2T fixed |

## Complementary

|                        |          |
|------------------------|----------|
| Location of connection | Rear     |
| Localisation on device | Upside   |
| Connection position    | Vertical |
| Connection pitch       | 70 mm    |

## Packing Units

|                              |          |
|------------------------------|----------|
| Unit Type of Package 1       | PCE      |
| Number of Units in Package 1 | 1        |
| Package 1 Weight             | 2.684 kg |
| Package 1 Height             | 2 cm     |

|                  |        |
|------------------|--------|
| Package 1 width  | 8.7 cm |
| Package 1 Length | 28 cm  |

Offer Sustainability

|                            |                                                                                                                             |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| REACH Regulation           | <a href="#">REACH Declaration</a>                                                                                           |
| REACH free of SVHC         | Yes                                                                                                                         |
| EU RoHS Directive          | Compliant<br><a href="#">EU RoHS Declaration</a>                                                                            |
| Toxic heavy metal free     | Yes                                                                                                                         |
| Mercury free               | Yes                                                                                                                         |
| RoHS exemption information | <a href="#">Yes</a>                                                                                                         |
| China RoHS Regulation      | <a href="#">China RoHS declaration</a>                                                                                      |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|