

Product datasheet

Specifications



PLATE TRI 25 A H 105MM

Local distributor code: 386283266 AK5PA231

Main

Range	Linergy
Product name	HK
Product or component type	Mounting plate
Poles description	3P
[Ith] conventional free air thermal current	25 A
I²t on activation	200000 A².s
Number of cables	3 cable(s) 4 mm² at 105 °C
Width	54 mm
Height	105 mm
Depth	61 mm

Complementary

[Ui] rated insulation voltage	690 V conforming to IEC 60439-1
9 mm pitches	6
Net weight	0.145 kg

Environment

Standards	IEC 60439
Product certifications	DNV LROS (Lloyds register of shipping) UL CSA

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	224.0 g
Package 1 Height	6.5 cm
Package 1 width	7.5 cm
Package 1 Length	13.5 cm
Unit Type of Package 2	P06

Number of Units in Package 2	320
Package 2 Weight	85.884 kg
Package 2 Height	77 cm
Package 2 width	60 cm
Package 2 Length	80 cm
Unit Type of Package 3	S03
Number of Units in Package 3	40
Package 3 Weight	9.496 kg
Package 3 Height	30 cm
Package 3 width	30 cm
Package 3 Length	40 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------