

Product datasheet

Specifications



TeSys GC & GY - auxiliary contacts block - 1 NO + 1 NC

Local distributor code: 386284430 GAC0521

Main

Range	TeSys
Device short name	GAC0
Product or component type	Auxiliary contact block
Product compatibility	TeSys GC TeSys GY
Mounting location	Right side
Pole contact composition	1 NO + 1 NC
[Ue] rated operational voltage	250 V
[Ith] conventional free air thermal current	5 A (at 50 °C)

Complementary

[Ui] rated insulation voltage	500 V conforming to IEC 60947-5 500 V conforming to VDE 0110
Mechanical durability	1 Mcycles
Connections - terminals	Screw clamp terminals2.5 mm²solid Screw clamp terminals2.5 mm²flexible
Tightening torque	0.8 N.m - on screw clamp terminals
Height	81 mm
Width	8.75 mm
Depth	60 mm
Net weight	0.016 kg

Environment

Standards	IEC 60947-5
Product certifications	CEBEC OVE VDE NF-USE
IP degree of protection	IP20 conforming to VDE 0106
Protective treatment	TC
Ambient air temperature for operation	-5...50 °C

Ambient air temperature for storage	-40...70 °C
Operating altitude	<= 3000 m without derating
Packing Units	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	44.0 g
Package 1 Height	2.1 cm
Package 1 width	7.5 cm
Package 1 Length	8.6 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	506.0 g
Package 2 Height	8.2 cm
Package 2 width	9.6 cm
Package 2 Length	23 cm
Unit Type of Package 3	S03
Number of Units in Package 3	80
Package 3 Weight	4.548 kg
Package 3 Height	30 cm
Package 3 width	30 cm
Package 3 Length	40 cm
Offer Sustainability	
Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free product
Contractual warranty	
Warranty	18 months