

Product datasheet

Specifications



Auxiliary contacts, TeSys GS, 1 NO, early break, front mounting, for GS2 with front/side handle

Local distributor code: 386284634 GS1AM110

Main

Range of product	TeSys
Device short name	GS1AM
Product or component type	Auxiliary contact
Contact application	O, I and test position signalling
Range compatibility	TeSys GS fuse-switch disconnecter FuPacT GS fuse-switch disconnecter
Contacts type and composition	1 NO
Contact operation	Early-break
[Ith] conventional free air thermal current	10 A (at 40 °C)
[Ie] rated operational current	6 A at 120 V AC-15 3 A at 240 V AC-15 1.8 A at 400 V AC-15 1.5 A at 480 V AC-15 2.8 A at 24 V DC-13 1.4 A at 48 V DC-13 0.55 A at 125 V DC-13 0.27 A at 250 V DC-13 0.15 A at 400 V DC-13

Complementary

Mechanical durability	5 Mcycles
Electrical durability	1 Mcycles AC-15
Switch rated current	30 A 32 A 50 A 60 A 63 A 100 A 125 A 160 A 200 A 250 A 315 A 400 A 600 A 630 A 800 A 1250 A
Fuse type	NFC DIN BS CC J
Type of operating handle	External frontal External right side

	External left side
Mounting location	Front face
Net weight	0.015 kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	12.0 g
Package 1 Height	2 cm
Package 1 width	8 cm
Package 1 Length	9 cm
Unit Type of Package 2	S01
Number of Units in Package 2	40
Package 2 Weight	709.0 g
Package 2 Height	15 cm
Package 2 width	15 cm
Package 2 Length	40 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Contractual warranty

Warranty	18 months
----------	-----------