

Product datasheet

Specifications



Powerpact 4 - panelboard - 630A - 12 ways - 3P - Style D

Local distributor code: 387298920 MG6C12

Main

Range	PowerPact
Product or component type	Panelboard
Product name	PowerPact 4
Device application	Distribution
Colour	Cream (RAL 9001)
Provided equipment	removable bottom gland plate end cover

Complementary

[In] rated current	630 A
Number of ways	36 ways (1P) 12 ways (3P)
[Ue] rated operational voltage	415 V 50 Hz AC
Breaking capacity	36 kA AC 1 s
Enclosure material	epoxy-polyester powder steel
Thickness	Cover: 1.2 mm Enclosure: 1.6 mm
Cable entry	Bottom at main
Device mounting	Wall mounted
Height	1493 mm
Width	850 mm
Depth	260 mm
Horizontal fixing centres	710 mm
Vertical fixing centres	1350 mm

Environment

IP degree of protection	IP3x
Standards	BS EN 61439-1

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
Package 1 Weight	82.0 kg
Package 1 Height	44.5 cm
Package 1 width	160 cm
Package 1 Length	100 cm
Unit Type of Package 2	PAL
Number of Units in Package 2	1
Package 2 Weight	82.0 kg
Package 2 Height	44.5 cm
Package 2 width	160 cm
Package 2 Length	100 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------