

Product datasheet

Specifications



MGF fusegear switch disconnecter 250A TP&N, AC-23B, M10, 415 V, 50/60 Hz

Local distributor code: 387294571 MGFD2503C

Main

Range	MGF fusegear
Product or component type	Enclosed switch-disconnector
[Ue] rated operational voltage	415 V
[Ie] rated operational current	250 A

Complementary

Mechanical interlocking	Door interlocking function
Poles description	3P + N
Network type	AC
Network frequency	50/60 Hz
Utilisation category	AC-23B
[Uimp] rated impulse withstand voltage	8 kV
[Icw] rated short-time withstand current	5.23 kA
[Icm] rated short-circuit making capacity	8 kA
Maximum power	130 kW
Connections - terminals	Terminal stud 120 mm² M10 30 mm
Control type	Handle
Provision for padlocking	Handle padlockable in on and off position
Enclosure material	Steel epoxy-polyester powder cream RAL 9001
Provided equipment	Earthing kit Removable gland plates

Environment

Standards	BS EN 60947-3
-----------	---------------

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Contractual warranty	
Warranty	18 months