

Product datasheet

Specifications



MGF fusegear switch disconnecter 250A TP&N, AC-23B, M10, 415 V, 50/60 Hz

Local distributor code: 387294885 MGFS2503C

Main

Range	MGF fusegear
Product or component type	Enclosed fuse-switch-disconnector
[Ue] rated operational voltage	415 V
[Ie] rated operational current	250 A
Breaking capacity	50 kA Icn

Complementary

Mechanical interlocking	Door interlocking function
Poles description	3P + N
Network type	AC
Network frequency	50/60 Hz
Utilisation category	AC-23B
[Uimp] rated impulse withstand voltage	8 kV
[Icw] rated short-time withstand current	5.23 kA
[Icm] rated short-circuit making capacity	8 kA
Maximum power	130 kW
Connections - terminals	Terminal stud 120 mm² M10 30 mm
Fuse type	BS88
Fuse size	B3
Associated fuse rating	250 A
Control type	Handle
Provision for padlocking	Handle padlockable in on and off position
Enclosure material	Steel epoxy-polyester powder cream RAL 9001
Provided equipment	Fuse links Removable gland plates Earthing kit

Environment

Standards	BS EN 60947-3
-----------	---------------

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------