

# PC box IP66 IK08 RAL7035 Int.H325W275D120 Ext.H341W291D128 opaque PC cover H20

Local distributor code: 387531894 NSYTBP342912

| VI | a | ı | r |  |
|----|---|---|---|--|
|    |   |   |   |  |

| _                   |  |
|---------------------|--|
| Range               | Thalassa                               |
| Product name        | Thalassa TBP                           |
| Device application  | Multi-purpose                          |
| Category            | Industrial box                         |
| Height              | 341 mm                                 |
| Width               | 291 mm                                 |
| Depth               | 128 mm                                 |
| Internal height     | 325 mm                                 |
| Internal width      | 275 mm                                 |
| Internal depth      | 120 mm                                 |
| Enclosure mounting  | Wall mounted                           |
| Device composition  | 1 body                                 |
|                     | 1 cover                                |
|                     | 4 cover screw                          |
| Body type           | One piece moulded                      |
| Type of front cover | Low plain cover                        |
| Cover fixing        | Plastic screws                         |
| Lock type           | Captive screw flat outside sealed area |
| Removable parts     | Cover by captive screws                |

#### Complementary

| Material                    | Polycarbonate   |
|-----------------------------|---|
| Colour                      | Grey (RAL 7035)   |
| Standards                   | IEC 62208<br>UL 508 A                                       |
| Product certifications      | TÜV<br>UL   |
| Electrical insulation class | Class II  |
| Mounting location           | Outdoor (with canopy or shelter and anticondensation valve) |
| Net weight                  | 1.16 kg   |
|                             |   |

#### **Environment**

| IP degree of protection             | IP66 conforming to NEMA 4.4X |
|-------------------------------------|------------------------------|
| IK degree of protection             | IK08 conforming to IEC 62262 |
| Fire resistance                     | 960 °C                       |
| Ambient air temperature for storage | -1560 °C                     |
| Operating temperature               | -2580 °C                     |

# **Packing Units**

| PCE     |
|---------|
| 1       |
| 1.16 kg |
| 12.8 cm |
| 29.1 cm |
| 34.1 cm |
|         |

## Offer Sustainability

| ·                          |  |
|----------------------------|--|
| Sustainable offer status   | Green Premium product  |
| REACh Regulation           | REACh Declaration  |
| REACh free of SVHC         | Yes  |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration           |
| Toxic heavy metal free     | Yes  |
| Mercury free               | Yes  |
| RoHS exemption information | Yes  |
| China RoHS Regulation      | China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope) |
| Environmental Disclosure   | Product Environmental Profile  |
| Circularity Profile        | End of Life Information  |
|                            |  |

### **Contractual warranty**

| Truit and |
|-----------|
|-----------|