



Socket, separate contact, 10 A, relay type RXM3, screw connector, 250 V AC

Local distributor code: 388198252 RXZE2S114M

Main

Range of product	Harmony Electromechanical Relays Harmony Timer Relays
Product or component type	Socket
Contact terminal arrangement	Separate
Product compatibility	Plug-in relay RXM with 4 C/O contact Plug-in relay REXL with 4 C/O contact
Shape of pin	Flat
Device short name	RXZ
Sale per indivisible quantity	10

Complementary

10 A
< 250 V
Connector, 1 x 0.251 x 2.5 mm² (AWG 22AWG 14) flexible with cable end Connector, 2 x 0.252 x 1 mm² (AWG 22AWG 17) flexible with cable end Connector, 1 x 0.51 x 2.5 mm² (AWG 20AWG 14) solid without cable end Connector, 2 x 0.52 x 1.5 mm² (AWG 20AWG 16) solid without cable end
< 1 N.m for M3 screw(s)
By screw (panel) Clip-on (35 mm symmetrical DIN rail)
CE
27 mm
0.07 kg

Environment

Standards	IEC 61984
Product certifications	CSA Lloyd's UL
Ambient air temperature for storage	-4085 °C
Ambient air temperature for operation	-4055 °C
IP degree of protection	IP20 conforming to EN/IEC 60529

Dielectric strength	2500 V
De aline Huite	
Packing Units	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	62.2 g
Package 1 Height	2.679 cm
Package 1 width	2.893 cm
Package 1 Length	8.219 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	664.5 g
Package 2 Height	6.6 cm
Package 2 width	11.4 cm
Package 2 Length	13.7 cm
Unit Type of Package 3	S03
Number of Units in Package 3	200
Package 3 Weight	13.2 kg
Package 3 Height	30 cm
Package 3 width	30 cm
Package 3 Length	40 cm
Offer Sustainability	
Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration

RoHS exemption information

REACh free of SVHC

EU RoHS Directive

Mercury free

Toxic heavy metal free

China RoHS Regulation

Environmental Disclosure

Yes

Yes

Yes

Yes

EU RoHS Declaration

China RoHS declaration

Product Environmental Profile


141	40 months
Warranty	18 months

Pro-active compliance (Product out of EU RoHS legal scope)

Dimensions Drawings

Socket

Socket with Separate Contact Terminals and Connector for 4 Timed C/O Contacts



- 1 Relay
- 2 Protection Module
- 3 Carriage Stirrup
- 5 2 Links connection