## ClimaSys forced vent. IP54, 165m3/h, 115V, with outlet grille and filter G2

Local distributor code: 388827581 NSYCVF165M115PF

## Main

Range	ClimaSys
Product name	ClimaSys CV
Product or component type	Fan
Type of filter	Standard
Flow rate	Free flow rate with standard filter: 165 m3/h at 50 Hz Free flow rate with standard filter: 193 m3/h at 60 Hz
[Us] rated supply voltage	75126 V
Input voltage	115 V 50/60 Hz

Complementary	
Absorbed power	15.5 W 50 Hz 14.4 W 60 Hz
[In] rated current	0.2 A 50 Hz 0.18 A 60 Hz
Noise level < at	5051 dB
Bearing type	Ball
Height	268 mm external:
Width	248 mm external:
Depth	104 mm external:
Cut-out dimensions	223 x 223 mm
Net weight	1.14 kg
Material	Outlet grille: injected thermoplastic (ASA PC)
Colour	Outlet grille: grey (RAL 7035)
Ambient air temperature for operation	-2060 °C
Ambient air temperature for storage	-4070 °C
Maximum pressure	50 Pa flow rate 0 m³/h
Connections - terminals	Faston connector
IP degree of protection	IP54

1 axial motor

1 filter: front of axial motor 1 outlet grille: front

2 protective grille: on the front and rear surfaces

**Device composition** 

	1 cut-out template 1 power cord	
Condition of use	Outside temperature must be 5 °C lower than inside temperature	
	Filter must be cleaned and replaced regularly	
	Overfrequent filter replacement should be avoided	
	Flow rates depends on the work point, see ProClima software	
	Surrounding environment must be relatively clean	

	• •	
Pac	kına	Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	1.4 kg
Package 1 Height	19 cm
Package 1 width	25.5 cm
Package 1 Length	27.5 cm
Unit Type of Package 2	CAR
Number of Units in Package 2	1
Package 2 Weight	1.4 kg
Package 2 Height	14.2 cm
Package 2 width	25 cm
Package 2 Length	25 cm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
<b>Environmental Disclosure</b>	Product Environmental Profile
Circularity Profile	End of Life Information

## **Contractual warranty**

Warranty	18 months
----------	-----------