

Product datasheet

Specifications



ClimaSys forced vent. IP54, 85m³/h, 115V, with outlet grille and filter G2

Local distributor code: 388829204 NSYCVF85M115PF

Main

Range	ClimaSys
Product name	ClimaSys CV
Product or component type	Fan
Type of filter	Standard
Flow rate	Free flow rate with standard filter: 79 m ³ /h at 50 Hz Free flow rate with standard filter: 92 m ³ /h at 60 Hz
[Us] rated supply voltage	75...126 V
Input voltage	115 V 50/60 Hz

Complementary

Absorbed power	15 W 60 Hz 16 W 50 Hz
[In] rated current	0.207 A 50 Hz 0.179 A 60 Hz
Noise level < at	46...49 dB
Bearing type	Ball
Height	170 mm external:
Width	150 mm external:
Depth	62 mm external:
Cut-out dimensions	125 x 125 mm
Net weight	0.78 kg
Material	Outlet grille: injected thermoplastic (ASA PC)
Colour	Outlet grille: grey (RAL 7035)
Ambient air temperature for operation	-20...60 °C
Ambient air temperature for storage	-40...70 °C
Maximum pressure	50 Pa flow rate 0 m ³ /h
Connections - terminals	Faston connector
IP degree of protection	IP54
Device composition	1 axial motor 2 protective grille: on the front and rear surfaces 1 filter: front of axial motor 1 outlet grille: front

1 cut-out template
1 power cord

Condition of use	Overfrequent filter replacement should be avoided Surrounding environment must be relatively clean Outside temperature must be 5 °C lower than inside temperature Flow rates depends on the work point, see ProClima software Filter must be cleaned and replaced regularly
-------------------------	---

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	860.0 g
Package 1 Height	9 cm
Package 1 width	15.5 cm
Package 1 Length	18 cm
Unit Type of Package 2	CAR
Number of Units in Package 2	24
Package 2 Weight	23.034 kg
Package 2 Height	40 cm
Package 2 width	34.5 cm
Package 2 Length	24 cm
Unit Type of Package 3	PAL
Number of Units in Package 3	240
Package 3 Weight	250.0 kg
Package 3 Height	100 cm
Package 3 width	120 cm
Package 3 Length	240 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Contractual warranty

Warranty	18 months
-----------------	-----------