

Product datasheet

Specifications



CENTER FEED UNIT 160 A

Local distributor code: 389351959 KNA160ABT4



Main

Range of product	Canalis
Product name	KN
Product or component type	Feed unit
BAR MATERIAL	Aluminium
Product compatibility	KN
[Ie] rated operational current	160 A
Mounting location	Central
Colour	White (RAL 9001)

Complementary

Protection type	Without protection
[Ue] rated operational voltage	230...500 V
Connections - terminals	Lug for 95 mm² flexible Lug for 95 mm² rigid
Control type	Without
Number of circuits	1
Provided equipment	End cover
Mounting mode	By clips
Mounting support	Busbar
Standards	IEC 61439-6 IEC 60439-2
Width	698 mm
Depth	122 mm
Height	243 mm
Net weight	5.5 kg

Environment

IP degree of protection	IP55 conforming to IEC 60529
IK degree of protection	IK08 conforming to IEC 62262

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	6.2 kg
Package 1 Height	13.5 cm
Package 1 width	24.5 cm
Package 1 Length	60 cm
Unit Type of Package 2	PAL
Number of Units in Package 2	12
Package 2 Weight	85.0 kg
Package 2 Height	85 cm
Package 2 width	62 cm
Package 2 Length	92 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free product

Contractual warranty

Warranty	18 months
----------	-----------