# **Product datasheet**

Specifications





# Auxiliary contact block, TeSys D, 2NO, front mounting, spring terminals

Local distributor code: 389740832 LADN203

#### Main

wain	
Range	TeSys TeSys Deca
Product name	TeSys D TeSys Deca
Product or component type	Auxiliary contact block
Device short name	LADN
Range compatibility	TeSys D CAD TeSys D LC1D TeSys Deca CAD TeSys Deca LC1D
Mounting location	Front
Pole contact composition	2 NO
Contacts operation	Instantaneous
[Ue] rated operational voltage	690 V AC 25400 Hz
[Ui] rated insulation voltage	690 V conforming to IEC 60947-5-1 600 V conforming to UL 600 V conforming to CSA
[Ith] conventional free air thermal current	10 A (at 60 °C)
Standards	EN/IEC 60947-5-1 UL 60947-5-1 CSA C22.2 No 60947-5-1 GB/T 14048.5 EN 50012
Product certifications	CB UL CSA CCC EAC UKCA

### Complementary

140 A AC conforming to IEC 60947-5-1 250 A DC conforming to IEC 60947-5-1
200 N 20 como mining to 120 coc n c n
100 A 60 °C 1 s 120 A 60 °C 500 ms 140 A 60 °C 100 ms
GG fuse 10 A
30 Mcycles
5 mA

Minimum switching voltage	17 V  1.5 ms on de-energisation no overlap between NC and NO contact 1.5 ms on energisation no overlap between NC and NO contact		
Non-overlap time			
Insulation resistance	> 10 MOhm		
Connections - terminals	Spring terminals 2 cable(s) 2.5 mm²flexible without cable end Spring terminals 2 cable(s) 2.5 mm²rigid		
Colour	Dark grey		
Height	48 mm		
Width	26 mm		
Depth	42 mm		

#### **Environment**

Environmental characteristic	Normal environment
IP degree of protection	IP20 conforming to IEC 60529
Protective treatment	TH conforming to IEC 60068
Ambient air temperature for storage	-6080 °C
Ambient air temperature for operation	-560 °C
Operating altitude	3000 m

## **Packing Units**

PCE
1
38.0 g
2.8 cm
4.2 cm
5.1 cm
BB1
10
381.0 g
2.8 cm
8.6 cm
25.5 cm
S02
160
6.547 kg
15 cm
30 cm
40 cm

# Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant

#### EU RoHS Declaration

Toxic heavy metal free	Yes Yes	
Mercury free		
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)	
Environmental Disclosure	Product Environmental Profile	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	

Warranty	18 months		
----------	-----------	--	--