

Product datasheet

Specifications



Ultimate Low profile - switched socket - 1 gang - chrome

Local distributor code: 391286708 GU3510WBC

Main

Aesthetic name	Low profile
Product or component type	Switched socket
Rated current	13 A at 230 V AC 50 Hz
Fixing mode	By screws M3.5 x 30 mm
Colour tint	Chrome

Complementary

Device presentation	Complete product
Outlet poles configuration	1P
Outlet standard description	3 pins
Outlet standard	British
Actuator	Rocker
Number of gangs	1 gang
Earth circuit	Standard earth
Pilot light	Without neon indicator
Device mounting	Wall mounted
Connections - terminals	Screw terminal
Material	Steel
Quantity per set	Set of 1
Height	88 mm
Width	88 mm
Depth	30 mm
Socket number	2

Environment

IP degree of protection	IP20
Standards	BS 1363

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
Package 1 Weight	163.0 g
Package 1 Height	4 cm
Package 1 width	9.5 cm
Package 1 Length	9.6 cm
Unit Type of Package 2	CAR
Number of Units in Package 2	100
Package 2 Weight	17.01 kg
Package 2 Height	22 cm
Package 2 width	42 cm
Package 2 Length	50 cm
Unit Type of Package 3	PAM
Number of Units in Package 3	1600
Package 3 Weight	292.1 kg
Package 3 Height	104.5 cm
Package 3 width	100 cm
Package 3 Length	120 cm

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration

Contractual warranty

Warranty	18 months
----------	-----------