

Product datasheet

Specifications



Ultimate Low profile - switched socket - 2 gangs - chrome

Local distributor code: 391286795 GU3520WBC

Main

Aesthetic name	Low profile
Product or component type	Switched socket
Rated current	13 A at 230 V AC 50 Hz
Fixing mode	By screws M3.5 x 30 mm
Colour tint	Chrome

Complementary

Device presentation	Complete product
Outlet poles configuration	1P
Outlet standard description	3 pins
Outlet standard	British
Actuator	Rocker
Number of gangs	2 gangs
Earth circuit	Standard earth
Pilot light	Without neon indicator
Device mounting	Wall mounted
Connections - terminals	Screw terminal
Material	Steel
Quantity per set	Set of 1
Height	88 mm
Width	148 mm
Depth	30 mm

Environment

IP degree of protection	IP20
Standards	BS 1363

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Package 1 Weight	267.0 g
Package 1 Height	15.5 cm
Package 1 width	3.9 cm
Package 1 Length	10.1 cm
Unit Type of Package 2	P12
Number of Units in Package 2	1000
Package 2 Weight	278.2 kg
Package 2 Height	115 cm
Package 2 width	100 cm
Package 2 Length	120 cm
Unit Type of Package 3	CAR
Number of Units in Package 3	50
Package 3 Weight	13.91 kg
Package 3 Height	17.5 cm
Package 3 width	44.2 cm
Package 3 Length	52.5 cm

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration

Contractual warranty

Warranty	18 months
----------	-----------