

Product datasheet

Specifications



MX shunt release, ComPacT NSX, rated voltage 380/415 VAC 50/60 Hz, 440/480 VAC 60 Hz, screwless spring terminal connections

Local distributor code: 391352700 LV429388

Main

Device short name	MX
Product or component type	Voltage release
Device application	Control
Range compatibility	ComPacT NSX new generation ComPacT NSX DC new generation ComPact NSX ComPact NSX DC EasyPact CVS PowerPact Multistandard
Voltage release type	Shunt trip release
[Uc] control circuit voltage	380...415 V AC 50 Hz 440...480 V AC 60 Hz

Complementary

Control signal type	Maintained Impulse
Impulse duration	>= 20 ms
Threshold tripping voltage	0.7...1.1 x Un opening
Supply inrush power	10 VA
Mounting mode	Fixed
Response time	50 ms
Auxiliary connection terminal	Spring 0.5...1.5 mm² (AWG 20...AWG 16)
Wire stripping length	7 mm

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	114.0 g
Package 1 Height	4.5 cm
Package 1 width	4.6 cm
Package 1 Length	6 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	10

Package 2 Weight	1.189 kg
Package 2 Height	7 cm
Package 2 width	10.5 cm
Package 2 Length	23.6 cm
Unit Type of Package 3	S03
Number of Units in Package 3	60
Package 3 Weight	7.515 kg
Package 3 Height	30 cm
Package 3 width	30 cm
Package 3 Length	40 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------