

Product datasheet

Specifications



External rotary handle, TeSys GS, black handle, front mounting, 2 positions I-O, IP65, for GS 100-400A IEC

Local distributor code: 393395189 GS2AH530

Main

Range of product	TeSys
Range	TeSys
Device short name	GS2AH
Product or component type	Rotary handle
Range compatibility	TeSys GS GS2J TeSys GS GS2K TeSys GS GS2L TeSys GS GS2N TeSys GS GS2P TeSys GS GS2Q FuPacT GS GSB100 FuPacT GS GSC125 FuPacT GS GSD125 FuPacT GS GSB160 FuPacT GS GSB200 FuPacT GS GSB250 FuPacT GS GSD250 FuPacT GS GSB400 FuPacT GS GSD400
Type of operating handle	External frontal
Handle colour	Black
Handle front plate colour	Grey

Complementary

Handle positions	O-I
Rotary handle padlocking	With
Switch rated current	100 A 125 A 160 A 200 A 250 A 315 A 400 A
Standards	IEC
Net weight	0.24 kg

Environment

IP degree of protection	IP65
-------------------------	------

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
Package 1 Weight	248.0 g
Package 1 Height	6 cm
Package 1 width	18.6 cm
Package 1 Length	16.9 cm
Unit Type of Package 2	S03
Number of Units in Package 2	20
Package 2 Weight	5.48 kg
Package 2 Height	30 cm
Package 2 width	30 cm
Package 2 Length	40 cm
Package 3 Height	30 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Contractual warranty

Warranty	18 months
----------	-----------