



## advantys STB communication module - for TeSys U - 24 V DC

Local distributor code: 393517983 LULC15

VI	а	ı	r	1

Range	TeSys
Device short name	LUL
Product or component type	Communication module
Product compatibility	LUCC LUCA LUCL LUCB LUCD
Device application	Communication
Range compatibility	TeSys U LUB non reversing power base TeSys U LU2B reversing power base

Complementary	
Main function available	Communication module
Mounting mode	Plug-in
Mounting location	Front side
Physical interface	CAN
Bus type	Advantys STB
Cable connector type	Fire wire
Communication port protocol	CAN2.B CAN2.0A
Addressing	Self-addressing
Transmission rate	800 kbit/s
Current consumption	1.5 mA at 24 V DC 2028 V
Logic input	Positive at 24 V DC - 7 mA
Response time	10 ms +/- 30 % change to state 0 10 ms +/- 30 % change to state 1
Input type	Resistive
Number of outputs	2 dedicated to starter-controller coil operation 1
[Us] rated supply voltage	24 V DC
Output current	<= 500 mA
Switching current capacity	0.5 mA at 24 V

Local signalling	3 LEDs front panel	
Connection pitch	3.81 mm	
Connections - terminals	Screw clamp terminals 1 cable(s) 0.141 mm²flexible without cable end Screw clamp terminals 1 cable(s) 0.141 mm²rigid without cable end Screw clamp terminals 1 cable(s) 0.250.5 mm²flexible with cable end Screw clamp terminals 1 cable(s) 0.251 mm²flexible with cable end Screw clamp terminals 2 cable(s) 0.140.5 mm²rigid without cable end Screw clamp terminals 2 cable(s) 0.140.75 mm²flexible without cable end Screw clamp terminals 2 cable(s) 0.250.34 mm²flexible with cable end Screw clamp terminals 2 cable(s) 0.5 mm²flexible with cable end	
Associated cable type	AWG 26AWG 16	
Tightening torque	0.20.25 N.m2.5 mm	
Environment		
Ambient air temperature for operation	-2555 °C	
IP degree of protection	IP20 conforming to IEC 60529	
Packing Units		
Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	106.0 g	
Package 1 Height	4.9 cm	
Package 1 width	4.9 cm	
Package 1 Length	11.3 cm	
Unit Type of Package 2	S02	
Number of Units in Package 2	35	
Package 2 Weight	4.065 kg	
Package 2 Height	15 cm	
Package 2 width	30 cm	
Package 2 Length	40 cm	
Offer Sustainability		
REACh Regulation	REACh Declaration	
EU RoHS Directive	Compliant EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	
Contractual warranty		
Warranty	18 months	