

Product datasheet

Specifications



Loadcenter, KQ B type, 3Phase, 250A ,18 TPN

Local distributor code: 396733133 SE54B250

Main

Range	Acti 9
Product name	Load centre KQ II B
Product or component type	Distribution board
Device application	Distribution
Enclosure type	Standard
Door type	Overall
Provided equipment	Enclosure Door Front cover Pan assembly Earth terminal block 25 mm² Shielded neutral bar 25 mm²

Complementary

Enclosure mounting	Surface
[Ie] rated operational current	250 A at 400/415 V AC
Incomer device options	Lugs Switch disconnecter - 4P Terminal block - 4P MCCB - 4P RCCB - 30 mA - 4P RCCB - 100 mA - 4P RCCB - 300 mA - 4P
Protection device options	Miniature circuit breaker (MCB) (plug-on type) as outgoer Residual current circuit breaker with overcurrent protection (RCBO) (plug-on type) as outgoer
Number of ways	18 ways (3P) outgoer
Cable entry	top and bottom: knock-out side: knock-out
Height	862 mm
Width	470 mm
Depth	139 mm

Environment

IP degree of protection	IP2x B internal conforming to BS EN 60529 IP3x external conforming to BS EN 60529
-------------------------	--

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	16.9 kg
Package 1 Height	15 cm
Package 1 width	49 cm
Package 1 Length	87 cm
Unit Type of Package 2	P12
Number of Units in Package 2	10
Package 2 Weight	189.0 kg
Package 2 Height	97 cm
Package 2 width	100 cm
Package 2 Length	120 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------