

Product datasheet

Specifications



auxiliary contact, Acti9, iOF/SD+OF, 2OC, AC/DC

Local distributor code: 396734938 A9A26929

Main

Range of product	Acti9
Product or component type	Double OC or fault contact
Device short name	IOF/SD+OF
Signal contacts composition	2 C/O
[In] rated current	1 A: 130 V DC 1.5 A: 60 V DC 2 A: 48 V DC 6 A: 24 V DC 3 A: 415 V AC - 50/60 Hz 6 A: 240 V AC - 50/60 Hz
9 mm pitches	1

Complementary

Range compatibility	Acti9 iSW-NA Acti9 iC60 Acti9 iC65 Acti9 iC60 RCBO Acti9 iID Acti 9 ARA Acti 9 RCA Acti 9 iDPN (China version) Acti9 iDPN Vig Acti 9 iC40
[Ui] rated insulation voltage	500 V
[Uimp] rated impulse withstand voltage	4 kV
Local signalling	Mechanical indicator
Mounting mode	Fixed
Mounting support	DIN rail
Comb busbar and distribution block compatibility	NO
Height	90 mm
Width	9 mm
Depth	73 mm
Net weight	43 g
Colour	White
Connections - terminals	Screw clamp terminal (top and bottom) 2 cable(s) 2.5 mm² - rigid Screw clamp terminal (top and bottom) 2 cable(s) 1.5 mm² - flexible with ferrule Screw clamp terminal (top and bottom) 1 cable(s) 0.5...2.5 mm² - flexible

	Screw clamp terminal (top and bottom) 1 cable(s) 1...4 mm² - rigid
Wire stripping length	10 mm
Tightening torque	1 N.m
Environment	
Standards	EN/IEC 60947-5-1
Tropicalisation	2 conforming to EN/IEC 60947-5-1
Ambient air temperature for operation	-35...70 °C
Ambient air temperature for storage	-40...85 °C
Packing Units	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	51.0 g
Package 1 Height	1.801 cm
Package 1 width	7.78 cm
Package 1 Length	9.285 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	12
Package 2 Weight	728.0 g
Package 2 Height	8.5 cm
Package 2 width	10 cm
Package 2 Length	27 cm
Unit Type of Package 3	CAR
Number of Units in Package 3	120
Package 3 Weight	7.43 kg
Package 3 Height	27.3 cm
Package 3 width	28.8 cm
Package 3 Length	38.6 cm
Offer Sustainability	
Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
------	---

Contractual warranty

Warranty	18 months
----------	-----------