



Acti9 centralized control and remote indication - iATLc+s

Local distributor code: 396735555 A9C15409

Main

Range of product	Acti 9	
Device short name	IATLc+s	
Product or component type	Centralized control and remote indication auxiliary	
Signal contacts composition	1 C/O	
Signalling circuit voltage	24 V AC/DC: 10 mA 12240 V AC: 50/60 Hz 6 A 1224 V DC: 6 A 15240 V AC: 50/60 Hz 2 A 1324 V DC: 2 A	
[Uc] control circuit voltage	24240 V AC 50/60 Hz	

Complementary

[Ui] rated insulation voltage	440 V	
[Uimp] rated impulse withstand voltage	4 kV	
Mounting mode	Fixed, on right side of TL	
Mounting support	DIN rail	
9 mm pitches	2	
Height	86 mm	
Width	18 mm	
Depth	71 mm	
Colour	White	
Connections - terminals	Tunnel type terminals0.54 mm² - rigid Tunnel type terminals0.54 mm² - rigid - with cable end Tunnel type terminals14 mm² - flexible Tunnel type terminals14 mm² - flexible - with cable end	
Wire stripping length	11 mm	
Tightening torque	1 N.m	
Range compatibility	Acti9 iTL iTL Acti9 iTL iTLi Acti9 iTL iTLs	
Product compatibility	ITL (32 A) ITL (16 A)	

Environment

Overvoltage category	III	
IP degree of protection	IP20 conforming to IEC 60529	
Tropicalisation	2	
Relative humidity	95 % at 55 °C	
Ambient air temperature for operation	-2050 °C	
Ambient air temperature for storage	-4070 °C	
Standards	EN/IEC 60669-2-2	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	74.0 g
Package 1 Height	2.9 cm
Package 1 width	8 cm
Package 1 Length	9 cm
Unit Type of Package 2	S03
Number of Units in Package 2	72
Package 2 Weight	6.391 kg
Package 2 Height	30 cm
Package 2 Height Package 2 width	30 cm 30 cm
Package 2 width	30 cm
Package 2 width Package 2 Length	30 cm 40 cm
Package 2 width Package 2 Length Unit Type of Package 3	30 cm 40 cm BB1
Package 2 width Package 2 Length Unit Type of Package 3 Number of Units in Package 3	30 cm 40 cm BB1 8
Package 2 width Package 2 Length Unit Type of Package 3 Number of Units in Package 3 Package 3 Weight	30 cm 40 cm BB1 8 656.0 g

Offer Sustainability Sustainable offer status

Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Compliant EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information	
Environmental Disclosure	Product Environmental Profile	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	
Halogen content performance	Halogen free plastic parts product	

Contractual warranty

144	40
Warranty	18 months