

Product datasheet

Specifications



Acti9 iIL Three-phase voltage indicator light - Red - 230-400 Vac

Local distributor code: 396736253 A9E18327

Main

Range of product	Acti 9
Product name	Acti9 iIL
Product or component type	Modular pilot lighth
Device short name	IIL
[Us] rated supply voltage	230...400 V AC at 50/60 Hz

Complementary

Indicator light	3 LEDs red, service life 100000 h of constant lighting efficiency (consumption 0.9 W)
Mounting mode	Fixed
Mounting support	Symmetrical DIN rail
Comb busbar and distribution block compatibility	Upside: ProDis
9 mm pitches	2
Height	82 mm
Width	18 mm
Depth	69.5 mm
Colour	White (RAL 9003)
Auxiliary connection terminal	Tunnel type terminal 1 cable(s) rigid 0.5 mm ² Tunnel type terminal 2 cable(s) rigid 2.5 mm ² Tunnel type terminal 1 cable(s) flexible 0.5 mm ² Tunnel type terminal 2 cable(s) flexible 2.5 mm ² Tunnel type terminal 2 cable(s) flexible with ferrule 2.5 mm ²
Wire stripping length	9 mm
Tightening torque	1 N.m

Environment

Standards	IEC 73 IEC 1000-4
IP degree of protection	IP2 IPxx B
Pollution degree	3
Tropicalisation	2
Relative humidity	95 % at 55 °C

Ambient air temperature for operation	-35...70 °C
---------------------------------------	-------------

Ambient air temperature for storage	-40...80 °C
-------------------------------------	-------------

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
------------------------------	---

Package 1 Weight	49.25 g
------------------	---------

Package 1 Height	2 cm
------------------	------

Package 1 width	6.5 cm
-----------------	--------

Package 1 Length	9 cm
------------------	------

Unit Type of Package 2	S03
------------------------	-----

Number of Units in Package 2	108
------------------------------	-----

Package 2 Weight	6.04 kg
------------------	---------

Package 2 Height	30 cm
------------------	-------

Package 2 width	30 cm
-----------------	-------

Package 2 Length	40 cm
------------------	-------

Unit Type of Package 3	BB1
------------------------	-----

Number of Units in Package 3	12
------------------------------	----

Package 3 Weight	628.0 g
------------------	---------

Package 3 Height	8 cm
------------------	------

Package 3 width	10 cm
-----------------	-------

Package 3 Length	23.5 cm
------------------	---------

Offer Sustainability

Sustainable offer status	Green Premium product
--------------------------	-----------------------

REACH Regulation	REACH Declaration
------------------	-----------------------------------

EU RoHS Directive	Compliant EU RoHS Declaration
-------------------	--

Mercury free	Yes
--------------	-----

RoHS exemption information	Yes
----------------------------	---------------------

China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
-----------------------	---

Environmental Disclosure	Product Environmental Profile
--------------------------	---

WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
------	---

Halogen content performance	Halogen free plastic parts & cables product
-----------------------------	---

Contractual warranty

Warranty	18 months
----------	-----------
