

# Product datasheet

Specifications



## LoadCentre KQ - distribution board - A type - single phase - 125A - 12 ways

Local distributor code: 396792255    SE125A12

### Main

|                           |                                                                                                                |
|---------------------------|----------------------------------------------------------------------------------------------------------------|
| Range                     | Acti 9                                                                                                         |
| Product name              | Load centre KQ II A                                                                                            |
| Product or component type | Distribution board                                                                                             |
| Device application        | Distribution                                                                                                   |
| Enclosure type            | Standard                                                                                                       |
| Door type                 | Overall                                                                                                        |
| Provided equipment        | Enclosure<br>Door<br>Front cover<br>Pan assembly<br>Earth terminal block 25 mm²<br>Shielded neutral bar 25 mm² |

### Complementary

|                                |                                                                                                                                                            |
|--------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Enclosure mounting             | Surface                                                                                                                                                    |
| [Ie] rated operational current | 125 A at 230/240 V AC                                                                                                                                      |
| Incomer device options         | Switch disconnecter - 2P<br>Terminal block - 2P<br>RCCB - 30 mA - 2P<br>RCCB - 100 mA - 2P<br>RCCB - 300 mA - 2P                                           |
| Protection device options      | Miniature circuit breaker (MCB) (plug-on type) as outgoer<br>Residual current circuit breaker with overcurrent protection (RCBO) (plug-on type) as outgoer |
| Number of ways                 | 12 ways (1P) outgoer                                                                                                                                       |
| Cable entry                    | top and bottom: knock-out<br>side: knock-out                                                                                                               |
| Height                         | 270 mm                                                                                                                                                     |
| Width                          | 376 mm                                                                                                                                                     |
| Depth                          | 127 mm                                                                                                                                                     |

### Environment

|                         |                                                                                      |
|-------------------------|--------------------------------------------------------------------------------------|
| IP degree of protection | IP2x B internal conforming to BS EN 60529<br>IP3x external conforming to BS EN 60529 |
|-------------------------|--------------------------------------------------------------------------------------|

### Packing Units

|                        |     |
|------------------------|-----|
| Unit Type of Package 1 | PCE |
|------------------------|-----|

|                              |            |
|------------------------------|------------|
| Number of Units in Package 1 | 1          |
| Package 1 Weight             | 4.765 kg   |
| Package 1 Height             | 13 cm      |
| Package 1 width              | 31 cm      |
| Package 1 Length             | 43 cm      |
| Unit Type of Package 2       | P12        |
| Number of Units in Package 2 | 56         |
| Package 2 Weight             | 292.664 kg |
| Package 2 Height             | 112 cm     |
| Package 2 width              | 100 cm     |
| Package 2 Length             | 120 cm     |

### Offer Sustainability

|                             |                                                                                                                       |
|-----------------------------|-----------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status    | Green Premium product                                                                                                 |
| REACH Regulation            | <a href="#">REACH Declaration</a>                                                                                     |
| EU RoHS Directive           | Pro-active compliance (Product out of EU RoHS legal scope)<br><a href="#">EU RoHS Declaration</a>                     |
| Mercury free                | Yes                                                                                                                   |
| RoHS exemption information  | <a href="#">Yes</a>                                                                                                   |
| China RoHS Regulation       | <a href="#">China RoHS declaration</a><br>Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure    | <a href="#">Product Environmental Profile</a>                                                                         |
| Halogen content performance | Halogen free plastic parts product                                                                                    |

### Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|