

# Isobar A - neutral bar - 1N - for distribution board - 10 ways SP+N

Local distributor code: 396793791 SEA9NA10

Maır	1

Range of product	Acti 9
Product or component type	Neutral bar
Enclosure mounting	Wall mounted
Door type	Overall
Enclosure material	Steel
Surface treatment	Ероху
Surface finish	Powder paint
Poles description	1P + N

## Complementary

[le] rated operational current	125 A at 230/240 V AC 125 A at 110 V AC	
Breaking capacity	25 kA	
Protection device name	IC60H	
Product destination	Distribution board	
Number of ways	10 ways outgoer	
Provided equipment	Neutral bar Busbar link 4 Cover	
IP degree of protection	IP2x internal conforming to BS EN 60529	
IK degree of protection	IK05 conforming to BS EN 60529	
Colour	White (RAL 9001)	

#### **Environment**

Standards	BS EN 60439-3
Ambient air temperature for operation	-3570 °C
Ambient air temperature for storage	-4080 °C

## **Packing Units**

Unit Type of Package 1	PCE			
------------------------	-----	--	--	--

Number of Units in Package 1	1	
Package 1 Weight	240.0 g	
Package 1 Height	9 cm	
Package 1 width	9 cm	
Package 1 Length	39 cm	
Offer Sustainability		
Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information	
Environmental Disclosure	Product Environmental Profile	

# **Contractual warranty**

Warranty	18 months
----------	-----------