

Product datasheet

Specifications



Isobar A - neutral bar - 1N - for distribution board - 18 ways SP+N



Local distributor code: 396793814 SEA9NA18

Main

Range of product	Acti 9
Product or component type	Neutral bar
Enclosure mounting	Wall mounted
Door type	Overall
Enclosure material	Steel
Surface treatment	Epoxy
Surface finish	Powder paint
Poles description	1P + N

Complementary

[Ie] rated operational current	125 A at 230/240 V AC 125 A at 110 V AC
Breaking capacity	25 kA
Protection device name	IC60H
Product destination	Distribution board
Number of ways	18 ways outgoer
Provided equipment	Neutral bar Busbar link 4 Cover
IP degree of protection	IP2x internal conforming to BS EN 60529
IK degree of protection	IK05 conforming to BS EN 60529
Colour	White (RAL 9001)

Environment

Standards	BS EN 60439-3
Ambient air temperature for operation	-35...70 °C
Ambient air temperature for storage	-40...80 °C

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
Package 1 Weight	319.8 g
Package 1 Height	8.1 cm
Package 1 width	8 cm
Package 1 Length	38.2 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------