

Product datasheet

Specifications



LoadCentre KQ - type B split metered distribution board - 125A - 12 + 8 TP ways

SEB36S24125

Main

Range	Acti 9
Product name	Load centre KQ II B
Product or component type	Distribution board
Device application	Distribution
Enclosure type	Split meter
Door type	Overall
Provided equipment	Enclosure Door Front cover Switch disconnecter - 125 A as incomer Multi-function meter - 2 nos. Shielded neutral bar 25 mm² Earth terminal block 25 mm² Pan assembly

Complementary

Enclosure mounting	Surface
[Ie] rated operational current	125 A at 400/415 V AC
Protection device options	Miniature circuit breaker (MCB) (plug-on type) as outgoer Residual current circuit breaker with overcurrent protection (RCBO) (plug-on type) as outgoer
Number of ways	12 ways (3P)outgoer for section 1 8 ways (3P)outgoer for section 2
Cable entry	top and bottom: knock-out side: knock-out
Height	1290 mm
Width	470 mm
Depth	139 mm

Environment

IP degree of protection	IP2x B internal conforming to BS EN 60529 IP3x external conforming to BS EN 60529
-------------------------	--

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	27.65 kg

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 1 Height	15 cm
Package 1 width	54 cm
Package 1 Length	134 cm
Unit Type of Package 2	PAL
Number of Units in Package 2	12
Package 2 Weight	341.8 kg
Package 2 Height	105 cm
Package 2 width	107 cm
Package 2 Length	150 cm

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information

Contractual warranty

Warranty	18 months
----------	-----------