

# Product datasheet

Specifications



## contactor iCT - 3 poles - 3 NO - 25 A - 220..240 V AC

Local distributor code: 396892744    A9C20833

### Main

|                                |                           |
|--------------------------------|---------------------------|
| Range of product               | Acti9                     |
| Product name                   | Acti9 iCT                 |
| Product or component type      | Contactors                |
| Device short name              | ICT                       |
| Device application             | Motor-heating-lighting    |
| Poles                          | 3P                        |
| [Ie] rated operational current | 25 A AC-7A<br>8.5 A AC-7B |
| Pole contact composition       | 3 NO                      |
| Network type                   | AC                        |
| Control type                   | Remote control            |
| [Uc] control circuit voltage   | 220...240 V AC 50 Hz      |

### Complementary

|                                        |                              |
|----------------------------------------|------------------------------|
| Network frequency                      | 50 Hz                        |
| [Ue] rated operational voltage         | 400 V AC 50 Hz               |
| Maximum power                          | 1.6 W at 400 V AC            |
| [Ui] rated insulation voltage          | 500 V AC 50/60 Hz            |
| [Uimp] rated impulse withstand voltage | 4 kV                         |
| Control signal type                    | Maintained                   |
| Switching frequency                    | 100 switching operations/day |
| Local signalling                       | Action indicator             |
| Hold-in power consumption in VA        | 4.6 VA                       |
| Inrush power in VA                     | 34 VA                        |
| Mounting mode                          | Clip-on                      |
| Mounting support                       | 35 mm symmetrical DIN rail   |
| 9 mm pitches                           | 4                            |
| Height                                 | 81 mm                        |

|                         |                                                                                                                                                                                                                                                                                                                                                            |
|-------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Width                   | 36 mm                                                                                                                                                                                                                                                                                                                                                      |
| Depth                   | 60 mm                                                                                                                                                                                                                                                                                                                                                      |
| Colour                  | White                                                                                                                                                                                                                                                                                                                                                      |
| Mechanical durability   | 1000000 cycles                                                                                                                                                                                                                                                                                                                                             |
| Electrical durability   | 100000 cycles IEC/EN 61095 25 A 50 Hz AC-7A<br>30000 cycles IEC/EN 61095 8.5 A 50 Hz AC-7B<br>30000 cycles IEC/EN 61095 50 Hz AC-7C<br>100000 cycles EN/IEC 60947-4-1 50 Hz AC-1<br>30000 cycles EN/IEC 60947-4-1 50 Hz AC-3<br>30000 cycles EN/IEC 60947-4-1 50 Hz AC-5a<br>30000 cycles EN/IEC 60947-4-1 50 Hz AC-5b                                     |
| Connections - terminals | Control circuit: tunnel type terminals2 cable(s) 1.5 mm² rigid<br>Power circuit: tunnel type terminals1 cable(s) 1...4 mm² flexible<br>Power circuit: tunnel type terminals1 cable(s) 1.5...6 mm² rigid<br>Control circuit: tunnel type terminals1 cable(s) 1.5...2.5 mm² rigid<br>Control circuit: tunnel type terminals2 cable(s) 1.5...2.5 mm² flexible |
| Tightening torque       | Control circuit: 0.8 N.m<br>Power circuit: 0.8 N.m                                                                                                                                                                                                                                                                                                         |
| Product compatibility   | IACtc<br>IACtp<br>IACts<br>IATet                                                                                                                                                                                                                                                                                                                           |
| Compatibility code      | ICT                                                                                                                                                                                                                                                                                                                                                        |
| Market segment          | Small commercial<br>Residential                                                                                                                                                                                                                                                                                                                            |

## Environment

|                                       |                                                                                      |
|---------------------------------------|--------------------------------------------------------------------------------------|
| Standards                             | IEC/EN 61095                                                                         |
| Noise level                           | 30 dB                                                                                |
| Heat dissipation                      | 1.6 W at 50/60 Hz                                                                    |
| IP degree of protection               | IP20 conforming to IEC 60529<br>IP40 (modular enclosure) conforming to IEC 60529     |
| Pollution degree                      | 2                                                                                    |
| Tropicalisation                       | 2 conforming to EN 60947-4-1<br>2 conforming to EN 61095<br>2 conforming to IEC 1095 |
| Relative humidity                     | 95 % at 55 °C                                                                        |
| Operating altitude                    | 2000 m                                                                               |
| Ambient air temperature for operation | -5...60 °C                                                                           |
| Ambient air temperature for storage   | -40...70 °C                                                                          |

## Packing Units

|                              |          |
|------------------------------|----------|
| Unit Type of Package 1       | PCE      |
| Number of Units in Package 1 | 1        |
| Package 1 Weight             | 227.0 g  |
| Package 1 Height             | 4 cm     |
| Package 1 width              | 11.2 cm  |
| Package 1 Length             | 12.2 cm  |
| Unit Type of Package 2       | S03      |
| Number of Units in Package 2 | 36       |
| Package 2 Weight             | 9.043 kg |
| Package 2 Height             | 30 cm    |

|                              |          |
|------------------------------|----------|
| Package 2 width              | 30 cm    |
| Package 2 Length             | 40 cm    |
| Unit Type of Package 3       | BB1      |
| Number of Units in Package 3 | 6        |
| Package 3 Weight             | 1.437 kg |
| Package 3 Height             | 11.5 cm  |
| Package 3 width              | 12.5 cm  |
| Package 3 Length             | 25 cm    |

### Offer Sustainability

|                            |                                                                                                                       |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                                                 |
| REACH Regulation           | <a href="#">REACH Declaration</a>                                                                                     |
| EU RoHS Directive          | Compliant<br><a href="#">EU RoHS Declaration</a>                                                                      |
| Mercury free               | Yes                                                                                                                   |
| RoHS exemption information | <a href="#">Yes</a>                                                                                                   |
| China RoHS Regulation      | <a href="#">China RoHS declaration</a><br>Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>                                                                         |

### Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|