

Product datasheet

Specifications



QOvs - earth leakage circuit breaker - 1P + Ns - C curve - 40A - 30mA

Local distributor code: 397134731 QO140C10RCBO30F

Main

Circuit breaker application	Distribution
Range	Square D
Product name	QOvs RCBO
Product or component type	Residual current breaker with overcurrent protection (RCBO)
Poles description	1P + Ns
[In] rated current	40 A at 40 °C
Earthing system	TN
Curve code	C
Earth-leakage sensitivity	30 mA
Breaking capacity	10000 A Icn at 230/240 V AC 50/60 Hz

Complementary

Number of protected poles	1
Device location in system	Outgoer
Network frequency	50/60 Hz
Network type	AC
Trip unit technology	Thermal-magnetic
[Ue] rated operational voltage	230/240 V AC 50/60 Hz
Residual current tripping technology	Voltage dependent functional earth
Earth-leakage protection time delay	Instantaneous
Earth-leakage protection class	Type AC
[Icw] rated short-time withstand current	Icw: 250 A during 8/20 µs impulse withstand
[Ics] rated service breaking capacity	7500 A at 230/240 V AC 50/60 Hz
Electrical insulation class	Class II
Limitation class	3
[Ui] rated insulation voltage	400 V AC 50/60 Hz

[Uimp] rated impulse withstand voltage	4 kV
Surge current	250 A
Suitability for isolation	Yes
Contact position indicator	Yes
Control type	Toggle
Local signalling	ON/OFF indication
Mounting mode	Plug-on
Mounting support	Socket
Comb busbar and distribution block compatibility	NO
Height	110 mm
Width	19 mm
Depth	85 mm
Net weight	186 g
Colour	Black
Mechanical durability	20000 cycles
Electrical durability	5000 cycles
Provision for padlocking	Non padlockable
Connections - terminals	Plug-in connector (top) Tunnel type terminal (bottom) 1...16 mm² rigid without cable end Tunnel type terminal (bottom) 1...10 mm² with cable end Tunnel type terminal (bottom) 1...10 mm² flexible without cable end
Wire stripping length	Power circuit: 15 mm for bottom connection
Tightening torque	Power circuit: 2 N.m bottom
Earth-leakage protection	Integrated

Environment

Standards	BS EN 61009-1 IEC 61009-2-2 IEC 61009-1 AS/NZS 61009.1
IP degree of protection	IP20
Tropicalisation	2
Relative humidity	95 % at 55 °C
Ambient air temperature for operation	-15...60 °C
Ambient air temperature for storage	-40...85 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	211.0 g
Package 1 Height	10.3 cm
Package 1 width	14.3 cm
Package 1 Length	2.7 cm
Unit Type of Package 2	P12

Number of Units in Package 2	1088
Package 2 Weight	229.568 kg
Package 2 Height	70 cm
Package 2 width	120 cm
Package 2 Length	80 cm
Unit Type of Package 3	S01
Number of Units in Package 3	17
Package 3 Weight	3.587 kg
Package 3 Height	15 cm
Package 3 width	15 cm
Package 3 Length	40 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------